

FILTERCARTIDGES

ÜBERSICHT

Type	Manufacturing	Efficiency	Material
FC 25xx/40xx FA	string - wound	80%	PP (polypropylene)
FC 25xx N90	melt blown	90%	PP
FC 25xx/40xx N95	melt blown	95%	PP
FC 40xxS N95	melt blown	95%	PP
FC 25xx A99	melt blown	99,8%	PP
FC 25xx QTEC	pleated	99,9% abs.	PE (polyethylene)
FC 25xx VTEC	pleated	99,99% abs	PE (polyester)
FC 55xx FO	melt blown	95%	PP
FC 60xx CL	melt blown	95%	PP
FC 25xx/40xx PES 5	pleated	85%	PES
FC 25xx/40xx PES 15	pleated	85%	PES
FC 25xx/40xx PES 30	pleated	85%	PES
FC 25xx NT	net	75%	Ny (nylon)
FC 25xx SS-P	net	75%	AISI 316
FC 25xx SS-S	net	75%	AISI 316
FC 25xx SSP-S	pleated	75%	AISI 316
FC 25xx SSP-P	pleated	75%	AISI 316
FC 25xx/40xx GAC	granulated	95%	AC (active carbon)
FC 25xx/40xx BAC	block	85%	AC
FC 25xx/40xx PAC	pleated	85%	AC-PE
FC 25xx/40xx CAC	block	85%	AC-CE