

# FILTERCARTRIDGES

## FC 25xx – N95

- melt blown polypropylen filtercartridge
- with depth filtration
- made from FDA approved polypropylen without additions or binders
- with internal core made from polypropylen
- optional different end caps

for the filtration

- in watertreatment
- in the food and beverage industry
- in the biotechnology
- in elektronik and nuklear industry
- for petrochemical industrie
- in the galvanic industry
- for fine chemicals



<b>Length</b>	<b>9 3/4"</b>	<b>20"</b>	<b>30"</b>	<b>40"</b>
	(248	508	762	1016 mm)
<b>End Cap Type</b>	<b>DOE, Code 3, Code 7 or Code 8</b>			
<b>Sealings</b>	<b>Buna N, Silicone or Viton</b>			
<b>Filterfiness</b>	<b>1, 5, 10, 20, 50 micron</b>			
<b>Filtrationefficiency</b>	<b>95%</b>			
<b>max. Pressure</b>	<b>6 bar</b>			
<b>max. Temperatur</b>	<b>80°C</b>			
<b>Outsidediameter</b>	<b>2,5" / 68mm</b>			
<b>Insidediameter</b>	<b>28 mm</b>			

**Initial-Differentialpressure 0,15 bar**  
**max. Differentialpressure 0.8 bar**

