

FILTERCARTRIDGES

FC 25xx / 40xx – PESA

- pleated polyester- filtercartridge
- with internal core made from polypropylene
- with filterfiness of 5-30-50 µm

for the filtration
- in watertreatment

Material	Polyester	
Length	9 ¾"	20"
	(248 mm)	(508 mm)
Adapter	DOE	
Filterfiness	5, 30, 50 micron	
Filtrationefficiency	85%	
max. Pressure	6 bar	
max. Temperatur	52 °C	
Outsidediameter	25 xx	2,5" / 63mm
	40xx	4" / 120 mm
Insidediameter	28 mm	

Initial-Differentialpressure 0,15 bar
max. Differentialpressure 0,8 bar

Type	Flow*	
	Ltr/ h	max. Ltr./h
FC 2509 PESA 5	1500	2500
FC 2509 PESA 30	2200	3500
FC 2509 PESA 50	2500	4000
FC 2520 PESA 5	3000	4500
FC 2520 PESA 30	4000	5500
FC 2520 PESA 50	4300	5500
FC 4009 PESA 5	1800	2500
FC 4009 PESA 30	2500	3500
FC 4009 PESA 50	2800	4000
FC 4020 PESA 5	3300	4500
FC 4020 PESA 30	4500	5500
FC 4020 PESA 50	4800	5500

* at 0,15 bar Ddifferentialpressure and 20 °C

Technical changes possible. Data given not to understand as warrantyfigures

