

# FILTERCARTRIDGES

## FC 25xx – SSP-S

- pleated stainless steel web filtercartridge
- made from AISI 316 ( 1.4571 )
- with internal core, end cap from stainless steel
- washable / backwash possible

for the filtration

- in watertreatment
- in the food and beverage industry
- in the biotechnology



|                             |   |            |            |            |
|-----------------------------|---|------------|------------|------------|
| <b>Length</b>               | <b>9 3/4"</b>                             | <b>20"</b> | <b>30"</b> | <b>40"</b> |
|                             | (248                                      | 508        | 762        | 1016 mm)   |
| <b>Filterfiness</b>         | <b>5, 10, 25, 40, 80, 100, 200 micron</b> |            |            |            |
| <b>Filtrationefficiency</b> | <b>75%</b>                                |            |            |            |
| <b>max. Pressure</b>        | <b>6 bar</b>                              |            |            |            |
| <b>max. Temperatur</b>      | <b>80 – 360 °C</b>                        |            |            |            |
| <b>Outsidediameter</b>      | <b>2,5" / 63mm</b>                        |            |            |            |
| <b>Insidediameter</b>       | <b>28 mm</b>                              |            |            |            |

**Initial-Differentialpressure 0,15 bar**  
**max. Differentialpressure 0,8 bar**

