

CABINET - SOFTENING Type *SOFT - CAB*

02/2003

Art. No.	Type	Description	Flow m ³ /h	Capacity m ³ x °dH	Resinvol. Ltr.	Fleck-Valve Type	Type
820 100	SOFT-CABmini	Standard - Kleinanlage	1,5	30	5	Autotrol D19	
820 130	SOFT-CAB S - 3	Standard - Cabinet	1,5	50	13	5600 zeit	A
820 140	SOFT-CAB S - 4	Standard - Cabinet	1,5	50	13	5600 vol	A
820 150	SOFT-CAB S - 5	Standard - Cabinet	1,5	50	13	5600SE vol	B
820 180	SOFT-CAB L - 3	Standard - Cabinet	2,0	80	18	5600 zeit	A
820 190	SOFT-CAB L - 4	Standard - Cabinet	2,0	80	18	5600 vol	A
820 200	SOFT-CAB L - 5	Standard - Cabinet	2,0	80	18	5600SE vol	B
820 230	SOFT-CAB XL - 3	Standard - Cabinet	2,6	110	25	5600 zeit	A
820 240	SOFT-CAB XL - 4	Standard - Cabinet	2,6	110	25	5600 vol	A
820 250	SOFT-CAB XL - 5	Standard - Cabinet	2,6	110	25	5600SE vol	B
820 280	SOFT-CAB XL - N3	Cabinet for Nitrateremoval	2,6	110	25	5600 zeit	A
820 290	SOFT-CAB XL - N4	Cabinet for Nitrateremoval	2,6	110	25	5600 vol	A
820 300	SOFT-CAB XL - N5	Cabinet for Nitrateremoval	2,6	110	25	5600SE vol	B
820 310	SOFT-CAB XL - N6	for Nitrateremoval-with DVGW Comp.	2,6	110	25	6665 HPE	B
820 320	SOFT-CAB XL - HPE	with DVGW-components	2,6	110	25	6665 HPE	B

Valvetype FLECK 5600, Material Noryl, electromechanical Controller - time controlled
FLECK 5600, Material Noryl, electromechanical Controller - volume controlled
FLECK 5600SE, Material Noryl, electronic Controller - volume controlled
FLECK 6665 HPE, Material Noryl, electronic Controller - volume controlled

Options on request against upcharge
- cocounter current operation
- additional elect. contact

** german authority approved

Technical changes possible.