

CABINET - SOFTENING Type *SOFT - CAB CL*

02/2003

Art. No.	Type	Description	Flow m ³ /h	Capacity m ³ x °dH	Resinvol. Ltr.	Fleck-Valve Type	Type
820 400	SOFT-CAB S - 3 CL	Standard - Cabinet	1,5	50	13	5600 zeit	A
820 405	SOFT-CAB S - 4 CL	Standard - Cabinet	1,5	50	13	5600 vol	A
820 410	SOFT-CAB L - 3 CL	Standard - Cabinet	2,0	80	18	5600 zeit	A
820 415	SOFT-CAB L - 4 CL	Standard - Cabinet	2,0	80	18	5600 vol	A
820 420	SOFT-CAB XL - 4 CL	Standard - Cabinet	2,6	110	25	5600 zeit	A
820 425	SOFT-CAB XL - 3 CL	Standard - Cabinet	2,6	110	25	5600 vol	A
820 430	SOFT-CAB XL - N3 CL	Cabinet for Nitrateremoval	2,6	110	25	5600 zeit	A
820 435	SOFT-CAB XL - N4 CL	Cabinet for Nitrateremoval	2,6	110	25	5600 vol	A

Valvetype CLACK - WS1 TC, Material Plastic, electromechanical Controller - time controlled
CLACK WS1 CL, Material Plastic, electromechanical Controller - volume controlled

Options on request against upcharge
- cocounter current operation
- additional elect. contact

Technical changes possible.