

MONEX - SOFTENING with CLACK Valves **1/2003**

Art. No.	Type	Flow* m³/h	Capacity m³ x °dH	Resin Ltr.	Fleck-Valve Type	Saltdemand kg/Reg**	Tank			Brinetank			Connections	
							Diameter***	Height***	Type	Volume/ ltr.	Diameter*	Height*	IN	OUT
840 510	MSP-25 CL	1 / 1,4	100	25	CL WS1	4	213	1113	RT 844	100	470	800	1" BSP	1" BSP
840 520	MSP-50 CL	2 / 2,8	200	50	CL WS1	8	259	1382	RT 1054	200	640	795	1" BSP	1" BSP
840 530	MSP-75 CL	3 / 4,2	300	75	CL WS1	12	333	1392	RT 1354	200	640	795	1" BSP	1" BSP
840 540	MSP-100 CL	4 / 5,6	400	100	CL WS1	16	356	1633	RT 1465	200	640	795	1" BSP	1" BSP

*at dP 1,0 / 1,8 bar

**at 160 gr/l

***in mm

Art. No.	Type	Installation area (ca. in mm)		
		length	depth	height
840 510	MSP-25 CL	1100	600	1300
840 520	MSP-50 CL	1400	800	1700
840 530	MSP-75 CL	1500	800	2100
840 540	MSP-100 CL	1600	800	2100

Scope of supply :

- 1 pcs PARK-GRP Pressure Tank
- 1 pcs CLACK- Central Control Valve
- 1 filling DOWEX - strong acid cation resin
- 1 pcs Brinetank with brinevalve, grid, brine well and cover
- 1 pcs Nozzles top and bottom
- 1 pcs Brine & Drain hose



The plant components are not assembled but packed together on a pallet

Technical changes possible.