



THIS DIMENSION CAN BE CHANGED WITH THE CUSTOMERS' REQUIREMENT

MODEL	A				VOLUME			DOME VOLUME			WEIGHT	
	mm	inch	+/- mm	+/- inch	Liters	U.S. GAL.	CUBIC FT	Liters	U.S. GAL.	CUBIC FT	Kg	LBS
9x17	431	16.97	4	0.16	13.7	3.62	0.48	1.30	0.34	0.05	2.25	4.96
9x35	896	35.28	4	0.16	31.6	8.35	1.12	1.30	0.34	0.05	4.20	9.25
9x42	1074	42.28	5	0.20	38.2	10.09	1.35	1.30	0.34	0.05	5.05	11.12
9x48	1228	48.35	5	0.20	44.6	11.78	1.58	1.30	0.34	0.05	6.05	13.33
9x18	459	18.07	4	0.16	14.7	3.88	0.52	1.30	0.34	0.05	2.42	5.33
9x40	1018	40.08	5	0.20	36.3	9.59	1.28	1.30	0.34	0.05	4.84	10.66
9x24	610	24.02	4	0.16	20.4	5.39	0.72	1.30	0.34	0.05	3.06	6.73
9x30	766	30.16	5	0.20	26.6	7.03	0.94	1.30	0.34	0.05	3.69	8.12

NOTES:

- TANK MUST MEET ALL APPLICABLE SPECIFICATIONS OF NSF/ANSI 044 STANDARD, LATEST REVISION.
- OPERATING SPECIFICATIONS:
 - MAXIMUM WORKING PRESSURE - 150 PSI (10.5BAR)
 - TEMPERATURE RANGE - 34-120° F (1-49°C)
 - MAXIMUM VACUUM - 5"Hg (127mm Hg)
- VISUAL LINER INSPECTION
 - NO MORE THAN 10 INTERNAL OR EXTERNAL BLEMISHES OR BURNT DEBRIS.
 - NO INTERNAL OR EXTERNAL BLEMISHES OR BURNT DEBRIS LARGER THAN 3×3mm.
 - NO INTERNAL BLEMISHES OR BURNT DEBRIS ALLOWED.
- ALL GLASS STRANDS FROM FIBERGLASS LINER TO BE BONDED AND COVERED.
- SURFACE TO BE FREE OF NICKS, SCRATCHES, RESIN AND GLASS.
- SURFACE FINISH.
- DIMENSIONS IN PARENTHESES ARE REFERENCE ONLY.
- DIMENSIONS IN SQUARE PARENTHESES ARE INCH UNIT.

NATURAL OR ALMOND INNER LINER

BLACK BASE